

## **TRUCK RIG**

# MOBILE B-54

# **Dynamic and Mobile**

Geotech's Mobile B-54 is mounted on an International chassis for easy and swift transportation. With the unique 3 winch system the B-54 has the ability to hang 23 meters of drill stem at a time, greatly increasing sampling speed. Outfitted with a Fraste breakout clamp this rig allows for quick and safe drill stem tripping. The B-54 is proficient in air rotary, mud rotary and coring; creating an effective geotechnical and environmental drill rig.

## **Depth Capabilities:**

Hollow stem augers (82.6 mm [3 1/4"] ID): Continuous flight auger (152.4 mm [6"] OD): **Continuous flight auger** (355.6 mm [14"] OD): 18.3 m (60') Rotary drilling (73 mm [2 7/8"] OD) drill rod: Diamond core drilling - N Wireline:

45.7 m (150') 91.4 m (300') 457 m (1,500') 365.8 m (1,200')

#### **Dimensions:**

**Width:** 2.43 m (8') **Length:** 9.14 m (30')

**Height:** 9.14 m (30') - Mast raised **Weight:** 14,061 kg (30,934 lbs)

#### **Rig Features:**

- Rotary Head Stroke: 3.65 m (12')
- Max torque spec of 8,611 ft/lbs
- Dump stroke 18"
- Mounted geotechnical auto drop hammer

Double clamp breakout system, reducing the need for pipe wrench usage

- Elevated work platform
- Rotary safety guard system

- Power: 262 hp
- Pull back 24,000 lbs
- Push force 16,000 lbs
- 3 winch system
- Outrigger system for additional stability

